



Three-Window Coupler



Key Features

- ◆ Low excess loss
- ◆ Low PDL
- ◆ Three operating windows
- ◆ High stability and reliability
- ◆ Mini size

Applications

Optical communication systems
CATV
FTTH

Package Dimensions & Pigtail Style

Package Dimensions	
Package A(Mini)	2.4mm x 35mm stainless steel tube
Package A	3.0mm x 48mm stainless steel tube
Package B	3.0mm x 55mm stainless steel tube
Package C	90mm x16mm x 9mm case
Pigtail Style	
Package A	250μM bare fiber
Package B	900μM loose tube
Package C	900μM loose tube or 2mm/3mm cable

*Other package dimensions can be made on customer request.

Ordering Information

WBC-	x-	X2-	345-	XX-	X-	XX-	xx-	x
	P:Premium A:Grade A X: On request	12:1X2 22:2X2	1310&1490 &1550nm	01: 01:99 02: 02:98 50: 50:50	1: 1 meter x: on request	25:250μM Fiber 09:900μM loose Fiber	SC:SC/UPC SA:SC/APC 00:no connect	A: A B: B C:C
	Grade	Port number	Operation Wavelength	coupling Ratio	Fiber length	Fiber type	Connect Type	Dimension

EX: WBC-P-12-345-50-1-25-00-A